

# Certificate Of Conformity to EN14960

This certificate relates only to the individual product detailed below. It confirms that at the time of manufacture this product conforms to EN14960.

This is the test certificate for your new inflatable. Please keep this in a safe place.

Product: 8ft Curved Play And Slide Clown (With Obstacles)

Serial No: P26688 Code: AQ5778SP1

Valid From: 10.10.2016

Certificate Number: P26688

Tag No:

| Product dimensions (m) |      |      |     |
|------------------------|------|------|-----|
| Н                      | W    | D    |     |
| 4.3                    | 4.42 | 4.65 |     |
| User Heights           |      |      |     |
| 1                      | 1.25 | 1.5  | 1.8 |
| User numbers           |      |      |     |
| 10                     | 8    | 6    | 5   |

### Unit Weight: 164 kg, Total 188 kg

| Structure                   | Pass | Fail | N/A |                                     |
|-----------------------------|------|------|-----|-------------------------------------|
| Security of Seams           | х    |      |     | Material = gloss 630g + 450g pvc    |
| Stitching                   | Х    |      |     |                                     |
| Anchor Points               | Х    |      |     | Anchor points= 14 pcs / metal triar |
| Anchor Accessories          | Х    |      |     |                                     |
| Walls & Towers              | х    |      |     | Inside heigh wall = 2.1 m           |
| Blower Tube(s)              | Х    |      |     | Blower tube length= 1.48 m          |
| Zip                         | Х    |      |     | Zips= 2 pcs (velcro flap+non return |
| Fabric Flame Retardant      | х    |      |     |                                     |
| Fabric Strength             | х    |      |     |                                     |
| Step / Ramp Size            | х    |      |     | Platform height = 0.6 m             |
| Grounding                   | х    |      |     |                                     |
| Sharp Angles                | Х    |      |     |                                     |
| Stability                   | х    |      |     |                                     |
| Ropes                       | Х    |      |     | Ropes= 2* 2m, diam. 10 mm - whi     |
| Artwork                     | х    |      |     | Artwork= printed+laq UV             |
| Air Loss Points             | х    |      |     |                                     |
| Water Gauge Pressure (WGP)  | Х    |      |     | WGP= 4.6 inch                       |
| Fall Off Height ( FOH )     |      |      | х   |                                     |
| Trough depth                | х    |      |     |                                     |
| Thread                      | Х    |      |     |                                     |
| Netting                     | Х    |      |     | Netting = black scrim fixed         |
| Entrapment                  | Х    |      |     |                                     |
| Deflation / Evacuation Time | х    |      |     |                                     |
| Windows                     |      |      | Х   |                                     |
| Markings                    | Х    |      |     |                                     |
| Identification              | Х    |      |     |                                     |

| Anchor points= 14 pcs / metal triangles                 |                         |
|---|-------------------------|
| Inside heigh wall = 2.1 m<br>Blower tube length= 1.48 m | Position= 2 pcs on rear |
| Zips= 2 pcs (velcro flap+non return flap)               |                         |
| Platform height = 0.6 m                                 |                         |
| Ropes= 2* 2m, diam. 10 mm - white                       |                         |
| Artwork= printed+laq UV                                 |                         |
| WGP= 4.6 inch   |                         |
| Netting = black scrim fixed                             | Roof= yellow 450g pvc   |

#### **Totally Enclosed Structures**

27 Exits

Ancl Wall 6 Blov 7 Zip 8 Fabi 9 Fabi 10

Stab 13 14 Rop 15 Artw 16

11

12

17 Wat 18 Fall

20

21 Nett

22 Entr 23

24

25

26

- Exit Markings 28 29
- Lighting Supports 30
- **Emergency Lighting**
- 31 Deflation Speed
- User Area Pressure

#### Slides

- 33 Wall Heights
- Run Out 34
- 35 Clamber step
- 36 Slide Sheet

## Blower

- Size & Type
- Inlet & Outlet Mesh
- Cable & Plug 39
- 40 Casing & Impeller
- 41 Pat Test
- 42 Return Flap

|  | , |  |
|--|---|--|
|  |   |  |

| Į |   |  |  |
|---|---|--|--|
|   |   |  |  |
|   | Х |  |  |
|   | X |  |  |

| х |  |
|---|--|
| х |  |
| Х |  |
| х |  |

| Height platform = 2.5 m |
|-------------------------|
| Wall height = 0.9 m     |
| Width of slide = 0.67 m |

| Height platform = 2.5 m |
|-------------------------|
| Wall height = 0.9 m     |
| Width of slide = 0.67 m |
| Run out = 1.8 m         |

| Mister |  |
|--------|--|
|        |  |
| 140163 |  |

Notes:

Slide sheet= red sliding material

Notes:

Accessories= 1x 7 m wiring harness, with EU plug + 1 x speaker + 1x disco light, with EU plug

**DEAK LORANT** 

RPII Annual Inflatable Inspector

Date of Test: 10.10.2016

**Duel House** Llandowlais Street Cwmbran NP44 7XB Tel: 01179 414 918 Fax: 01179 414 919

Email:

sales@airquee.co.uk



