

Certificate Of Conformity to EN14960:2019

This certificate relates only to the individual product detailed below. It confirms that at (R) the time of manufacture this product conforms to EN14960. To remain compliant this product must be tested annually.

To book your test please call +44 (0)1179 414 918 or visit www.airquee.com for more

This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.

**Product:** 12x12ft Jungle Curved Bouncer

Χ Χ

Χ Χ

Χ

Χ Χ

Χ Χ Χ

Χ Χ Χ

Χ Χ

Χ Χ Χ Χ

Χ Χ Χ Χ Χ

Pass Fail N/A

Serial No: P51744 A Code: A08394 Valid From: 28-09-2022

Certificate No: P51744 A

70kg Total: 79kg

				<u> </u>		
	Н	W	L			
	3.3	3.85	3.9			
		User He	ight (m)			
	1	1.25	1.5	1.8		
		Number	of Users			
	5	3	3	2		
ı	Votes			<u>.                                    </u>		
Material : gloss 630g pvc + gloss 520g printable						
Anchor points: 6 pcs PVC & metal triangle Bottom						
Supplied anchor accessories: 6 pcs / 400 mm* 18 r	nm metal pegs	;				
Inside wall height: 1.50 m						
Blower tube length: 1.47 m Position: 1 po Zips: 1 pcs (exterior velcro flap + interior non return						
Zips. 1 pcs (exterior veicro hap + interior horrietar	πι παρ)					
Platform height: 0.65 m Step depth: 1.1	.0 m					
Artwork : printed (laminated, UV resistant)						
kPa: 1.34						
FOH: 0.47 m						
Notting black serim fixed Poof - purple of	oss 4E0a DVC					
Netting: black scrim fixed Roof : purple gl	10SS 45UG PVC					
,	Notes					
	Notes	_	_	_		
ı	Notes					
Blower power: 1 pcs 1.5HP						

**Product Dimensions (m)** 

	<b>Tag No:</b> 56647
	Weight: Unit: 7
	Structure
1	Security Of Seems
2	Stitching
3	Anchor Points
4	Anchor Accessories
5	Walls & Towers
6	Blower Tube(s) / Valve(s)
7	Zip(s)
8	Fabric Flame Retardant
9	Fabric Strength
10	Step / Ramp Size
11	Grounding
12	Sharp Angles
13	Stability
	Ropes
15	Artwork
16	Air Loss Points
	Kilopascal (kPa)
	Fall Off Height (FOH)
	Trough Depth
	Thread
21	Netting
22	Entrapment
23	Deflation / Evacuation Time
	Windows
	Markings
26	Identification
	Totally Enclosed Structures
27	Exits

	,
14	Ropes
15	Artwork
16	Air Loss Points
17	Kilopascal (kPa)
18	Fall Off Height (FOH)
19	Trough Depth
20	Thread
21	Netting
22	Entrapment
23	Deflation / Evacuation Time
24	Windows
25	Markings
26	Identification
	Totally Enclosed Structures
27	Exits
28	Exit Markings
29	Lighting Supports
	Emergency Lighting
31	Deflation Speed
32	User Area Pressure
	Slides
33	Wall Height / Platform Height
34	Run-Out
	Clamber Step
36	Slide Sheet
	Blower
	Size & Type
	Inlet & Outlet Mesh
	Cable & Plug
	Casing & Impeller
41	Pat Test
42	Return Flap
cici	NED BY: Doák Loránt

	Х	
	Χ	
	Х	
	Χ	
	Χ	
	Χ	
	Χ	
	Χ	
	Χ	
	Χ	
Χ		Blower power: 1 pcs 1.5HP
Χ		
Χ		
Χ		
	Χ	
Χ		

	_^_
Х	
Х	
Х	
Х	
	Х
Х	

SIGNED BY: Deák Loránt RPII ANNUAL INFLATABLE INSPECTOR Airquee Ltd

Date of test: 22-09-2022

**Duel House** Llandowlais Street Cwmbran NP44 7XB, UK

Tel:+44 (0)1179 414 918 **Email:** sales@airquee.co.uk





To remain compliant this product must be tested annually.