

Certificate Of Conformity to EN14960

This certificate relates only to the individual product detailed below. It confirms that at the time of manufacture this product conforms to EN14960.

Product: Karting Track 15m x 15m

Serial No: P18922 Code: AQ3115

Valid From: 13.03.2015

Certificate Number: P18922

Product dimensions (m) W 2.35 15.15 15.35 **User Heights** 1.25 1.5 1.8

| Tag No: | | | | | | | User numbers | | ; |
|----------|--|--|------|--------|--|------------------|--------------|--|---|
| | _ | | | | Weight Unit 73 kg, Total 103 | ka | | | |
| | Structure | Pass | Fail | N/A | Troight ome to high rotal roo | Notes : | | | |
| 1 | Security of Seams | X | | .,,,, | Material = gloss 450g pvc | | | | |
| 2 | Stitching | Х | | | | | | | |
| 3 | Anchor Points | Х | | | Anchor points= 30 pcs/ triangles | | | | |
| 4 | Anchor Accessories | Х | | | | | | | |
| 5 | Walls & Towers | | | Х | | | | | |
| 6 | Blower Tube(s) | Х | | | | Position= 1 on r | ear | | |
| 7 | Zip | Х | | | Zips= 3 pcs(velcro flap+non return flap) | | | | |
| 8 | Fabric Flame Retardant | Х | | | | | | | |
| 9 | Fabric Strength | Х | | | | | | | |
| 10 | Step / Ramp Size | | | Х | | | | | |
| 11 | Grounding | | | Х | | | | | |
| 12 | | Х | | | | | | | |
| 13 | Stability | Х | | | | | | | |
| 14 | Ropes | | | Х | A 4 1 1 1 1 B 4 | | | | |
| | Artwork | Х | | | Artwork= manual paint + laq UV | | | | |
| | Air Loss Points | X | | | WGP= 6 inch | | | | |
| 17 | Water Gauge Pressure (WGP) Fall Off Height (FOH) | Х | | | WGP= 6 Inch | | | | |
| | Trough depth | <u> </u> | | X X | | | | | |
| 20 | Thread | Х | | | | | | | |
| 21 | Netting | _ ^ | | х | | | | | |
| | Entrapment | х | | | | | | | |
| 23 | Deflation / Evacuation Time | X | | | | | | | |
| 24 | Windows | | | Х | | | | | |
| 25 | Markings | х | | | | | | | |
| 26 | Identification | X | | | | | | | |
| | | | | | | | | | |
| | Totally Enclosed Structures | | | | | Notes : | | | |
| 27 | Exits | | | | | | | | |
| | Exit Markings | | | | | | | | |
| 29 | Lighting Supports | | | | | | | | |
| | Emergency Lighting | | | | | | | | |
| 31 | Deflation Speed | | | | | | | | |
| 32 | User Area Pressure | | | | | | | | |
| | Slides | | | | Notes : | | | | |
| 33 | Wall Heights | | | | | | | | |
| 34 | Run Out | | | | | | | | |
| 35 | Clamber step | | | | | | | | |
| 36 | Slide Sheet | | | | | | | | |
| Player | | | | | | Nets - : | | | |
| 27 | Blower Size & Type | v | | | Blower = power=1*1.5HP | Notes : | | | |
| | | Х | | | blower = power=1 1.5mP | | | | |
| 38 | Inlet & Outlet Mesh Cable & Plug | | | | | | | | |
| | Casing & Impeller | | | | | | | | |
| 40 41 | Pat Test | - | | | | | | | |
| | Return Flap | | | | | | | | |
| 44 | rectuin riap | | | | | | | | L |

Signed By:

Viore Constantin Tel: UK - 0845 0094 300 International +44 1179 414 918

Fax: UK - 0845 0095 300 International +44 1179 414 919 Address & Registered Office: Date of Test: 13.03.2015
Airquee Limited, Unit 2b, Barton Hill Trading Estate, Bristol, BS5 9RD, UK



